

WAKRA FB 216



FB216 / 18PS
Fugenbürstmaschine

- Ideal zum Reinigen und Auskehren von bereits geschnittenen Fugen
- Durch die gegenläufig arbeitende Bürste wird loses Material (Sand, kleine Steine oder Schneid-schlämme) aus der Fuge gekehrt
- Ultra moderne und kompakte Bauweise, wendig und leistungsstark
- Minimaler Platzbedarf auf der Baustelle und beim Transport
- Einfache Bedienung und gute Sicht auf das Bürstwerkzeug
- Optimaler Drehpunkt über zentrale Achse mit großen Rädern
- Tiefenverstellung über Kurbeltrieb und Wippe
- Vorderrad an der Wippe als Drehrolle gebaut und in der Linie mit der Werkzeugachse positioniert
- Schnelles Verschieben der Maschine ohne die Fugentiefe zu verstellen

Technische Daten / Technical data

WAKRA	FB 216-GX	FB 216
Benzinmotor, / Petrol engine	1-Zyl. Honda GX390 9.6kW, 13PS/HP, 3600 rpm	2-Zyl. V-Twin / 2-cyl. Vanguard 13.3kW, 18PS/HP, 3600 rpm
Bürstwerkzeug Ø / Brushing tool Ø	300mm	300mm
Diamant Sägeblatt Ø / Saw blade Ø	350mm	350mm
Arbeitstiefe / brushing depth	60mm	60mm
Tiefenverstellung / tool rising and lowering	über Kurbeltrieb und Wippe / mechanical depth adjustment	über Kurbeltrieb und Wippe / mechanical depth adjustment
Gewicht / Weight	ca. 125kg	ca. 145kg



FB216 / 13PS
Joint brushing machine

- Ideal for cleaning and sweeping out joints that have already been cut.
- The counter-rotating brush sweeps loose material (sand, small stones or cutting slurry) out of the joint
- Ultra-modern and compact design, manoeuvrable and powerful
- Minimal space requirement on the construction site and during transport
- Easy operation and good visibility of the brushing tool
- Optimal pivot point via central axle with large wheels
- Depth adjustment via crank drive and rocker arm
- Front wheel on the rocker built as a rotating roller and positioned in line with the tool axis
- Fast movement of the machine without adjusting the joint depth